## SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2015/830)

## SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1. Product identifier

Product name : DESODORISANT NOCTURNE 400ML VIS (A400VNOC)

Product code : CTG141657/0/01.

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

**1.3.** Details of the supplier of the safety data sheet

Registered company name : PRODIFA.

Address : ZAE Les Dix Muids. 59770 MARLY. France.

Telephone : +33 3 27 28 19 19 Fax : +33 3 27 28 19 10

info@prodifa.com

http://www.prodifa.com

#### 1.4. Emergency telephone number : +33 (0)1.45.42.59.59.

Association/Organisation : INRS/ORFILA http://www.centres-antipoison.net.

	· · · · · · · · · · · · · · · · · · ·					
SECTION 2 : HAZARDS	S IDENTIFICATION					
2.1. Classification of the	e substance or mixture					
In compliance with EC	regulation No. 1272/2008 and its amendments.					
Aerosol, Category 1 (A	Aerosol 1, H222 - H229).					
Eye irritation, Category	Eye irritation, Category 2 (Eye Irrit. 2, H319).					
May produce an allergi	ic reaction (EUH208).					
Hazardous to the aquat	tic environment - Chronic hazard, Category 3 (Aquatic Chronic 3, H412).					
2.2. Label elements						
Mixture for spray appli	ication.					
Mixture for aerosol app	plication.					
In compliance with EC	regulation No. 1272/2008 and its amendments.					
Hazard pictograms :						
GHS07 GHS	S02					
Signal Word :						
DANGER						
Additional labeling :						
EUH208	Contains OTNE [1-(1,2,3,4,5,6,7,8-OCTAHYDRO-2,3,8,8-TETRAMETHYL-2-NAPHTALENYL)-ETHANONE. May produce an allergic reaction.					
EUH208						
Hazard statements :						
H222	Extremely flammable aerosol.					
H229	Pressurised container: May burst if heated.					
H319	Causes serious eye irritation.					
H412	Harmful to aquatic life with long lasting effects.					
Precautionary statemer	nts - General :					
P101	If medical advice is needed, have product container or label at hand.					
P102	Keep out of reach of children.					

Precautionary statements - Prevention :	
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
Precautionary statements - Storage :	
P410 + P412	Protect from sunlight. Do no expose to temperatures exceeding 50 oC/122oF.
Precautionary statements - Disposal :	
P501	Eliminate the contents / container according to the local regulations.

#### 2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) >= 0.1% published by the European CHemicals Agency (ECHA) under article 57 of REACH: http://echa.europa.eu/fr/candidate-list-table

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

## SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

## 3.2. Mixtures

Composition :			
Identification	(EC) 1272/2008	Note	%
INDEX: 601_004_00_0	GHS02, GHS04	С	50 <= x % < 100
CAS: 106-97-8	Dgr	[1]	
EC: 203-448-7	Flam. Gas 1, H220	[7]	
REACH: 01-2119474691-32	Press. Gas, H280		
BUTANE			
INDEX: 603_002_005A	GHS07, GHS02	[1]	10 <= x % < 25
CAS: 64-17-5	Dgr		
EC: 200-578-6	Flam. Liq. 2, H225		
REACH: 01-2119457610-43	Eye Irrit. 2, H319		
ETHANOL			
INDEX: I54464_57_2	GHS07, GHS09		0 <= x % < 1
CAS: 54464-57-2	Wng		
EC: 259-174-3	Skin Irrit. 2, H315		
REACH: 01-2119489989-04	Skin Sens. 1B, H317		
	Aquatic Acute 1, H400		
OTNE	M Acute = 1		
[1-(1,2,3,4,5,6,7,8-OCTAHYDRO-2,3,8,8-TETR	Aquatic Chronic 1, H410		
AMETHYL-2-NAPHTALENYL)-ETHANONE	M Chronic $= 1$		
INDEX: A1222055	GHS09		0 <= x % < 1
CAS: 1222-05-5	Wng		
	Aquatic Acute 1, H400		
1.3.4.6.7.8-HEXAHYDRO-4.6.6.7.8.8-HEXAMT	M Acute = $1$		
YL-CYCLOPENTA-GAMMA-2-BENZOPYRA	Aquatic Chronic 1, H410		
NH	M Chronic $= 1$		
INDEX: I58567_11_6	GHS07, GHS09		$0 \le x \% < 1$
CAS: 58567-11-6	Wng		
EC: 261-332-1	Skin Irrit. 2, H315		
REACH: 01-2119971571-34	Skin Sens. 1B, H317		
	Aquatic Chronic 2, H411		
ETHOXY-METHYLCYCLODECYLETHER			

#### Information on ingredients :

[7] Propellant gas

[1] Substance for which maximum workplace exposure limits are available.

#### **SECTION 4 : FIRST AID MEASURES**

As a general rule, in case of doubt or if symptoms persist, always call a doctor. NEVER induce swallowing by an unconscious person.

THE VER induce swantowing by an unconscio

## 4.1. Description of first aid measures

## In the event of exposure by inhalation :

In the event of an allergic reaction, seek medical attention.

#### In the event of splashes or contact with eyes :

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.

If there is any redness, pain or visual impairment, consult an ophthalmologist.

#### In the event of splashes or contact with skin :

In the event of an allergic reaction, seek medical attention.

#### In the event of swallowing :

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.

Keep the person exposed at rest. Do not force vomiting.

Seek medical attention, showing the label.

If swallowed accidentally, call a doctor to ascertain whether observation and hospital care will be necessary. Show the label.

#### 4.2. Most important symptoms and effects, both acute and delayed

No data available.

#### 4.3. Indication of any immediate medical attention and special treatment needed

No data available.

#### SECTION 5 : FIREFIGHTING MEASURES

#### Flammable.

Chemical powders, carbon dioxide and other extinguishing gas are suitable for small fires.

#### 5.1. Extinguishing media

Keep packages near the fire cool, to prevent pressurised containers from bursting.

#### Suitable methods of extinction

In the event of a fire, use :

- sprayed water or water mist
- water with AFFF (Aqueous Film Forming Foam) additive
- halon
- foam
- multipurpose ABC powder
- BC powder
- carbon dioxide (CO2)

Prevent the effluent of fire-fighting measures from entering drains or waterways.

#### Unsuitable methods of extinction

In the event of a fire, do not use :

- water jet

#### 5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health. Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)
- carbon dioxide (CO2)

#### 5.3. Advice for firefighters

Due to the toxicity of the gas emitted on thermal decomposition of the products, fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus.

#### SECTION 6 : ACCIDENTAL RELEASE MEASURES

#### 6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

#### For non first aid worker

Because of the organic solvents contained in the mixture, eliminate sources of ignition and ventilate the area.

Avoid any contact with the skin and eyes.

#### For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

#### **6.2.** Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

If the product contaminates waterways, rivers or drains, alert the relevant authorities in accordance with statutory procedures Use drums to dispose of collected waste in compliance with current regulations (see section 13).

#### 6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

Use some absorbent.

The elimination must be carried out by a registrated salvage professionnal.

#### 6.4. Reference to other sections

No data available.

## SECTION 7 : HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

#### 7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Ensure that there is adequate ventilation, especially in confined areas.

Remove contaminated clothing and protective equipment before entering eating areas.

#### **Fire prevention :**

Handle in well-ventilated areas.

Vapours are heavier than air. They can spread along the ground and form mixtures that are explosive with air.

Prevent the formation of flammable or explosive concentrations in air and avoid vapor concentrations higher than the occupational exposure limits.

Do not spray on a naked flame or any incandescent material.

Do not pierce or burn, even after use.

Use the mixture in premises free of naked flames or other sources of ignition and ensure that electrical equipment is suitably protected.

Keep packages tightly closed and away from sources of heat, sparks and naked flames.

Do not use tools which may produce sparks. Do not smoke.

Prevent access by unauthorised personnel.

#### **Recommended equipment and procedures :**

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Do not breathe in aerosols.

Where the personnel must carry out work in a booth, whether for spraying or otherwise, the ventilation may be inadequate to control particles and solvent vapors in every case.

TMP No :

#### DESODORISANT NOCTURNE 400ML VIS - CTG141657/0/01

It is therefore recommended that personnel wear masks with a compressed air supply during spraying operations until the concentration of particles and solvent vapors has fallen below the exposure limits.

Avoid eye contact with this mixture.

Packages which have been opened must be reclosed carefully and stored in an upright position.

#### Prohibited equipment and procedures :

No smoking, eating or drinking in areas where the mixture is used.

Never open the packages under pressure.

#### 7.2. Conditions for safe storage, including any incompatibilities

No data available.

#### Storage

Keep out of reach of children.

Keep the container tightly closed in a dry, well-ventilated place.

Keep away from all sources of ignition - do not smoke.

Keep well away from all sources of ignition, heat and direct sunlight.

The floor must be impermeable and form a collecting basin so that, in the event of an accidental spillage, the liquid cannot spread beyond this area.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C.

#### Packaging

Always keep in packaging made of an identical material to the original.

#### 7.3. Specific end use(s)

No data available.

## SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1. Control parameters

## Occupational exposure limits :

#### - France (INRS - ED984 :2012) : CAS VME-ppm : VME-mg/m3 : VLE-ppm : VLE-mg/m3 : Notes : 106.97.8 200 1000

	106-97-8	800	1900	-	-	-	-
[	64-17-5	1000	1900	5000	9500	-	84
	- UK / WEL (Workplace exposure limits, EH40/2005, 2007) :						

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
106-97-8	600 ppm	750 ppm		Carc	
	1450 mg/m3	1810 mg/m3			
64-17-5	1000 ppm				
	1920 mg/m3				

#### Derived no effect level (DNEL) or derived minimum effect level (DMEL):

ETHANOL (CAS: 64-17-5)

Final use: Exposure method: Potential health effects: DNEL :

Exposure method: Potential health effects: DNEL :

Exposure method: Potential health effects: DNEL : Workers. Dermal contact. Long term systemic effects. 343 mg/kg body weight/day

Inhalation. Short term local effects. 1900 mg of substance/m3

Inhalation. Long term systemic effects. 950 mg of substance/m3

#### Final use:

Exposure method: Potential health effects: DNEL :

#### Predicted no effect concentration (PNEC):

ETHANOL (CAS: 64-17-5) Environmental compartment: PNEC :

Man exposed via the environment. Ingestion. Long term systemic effects. 87 mg/kg body weight/day

Dermal contact. Long term systemic effects. 206 mg/kg body weight/day

Inhalation. Short term local effects. 950 mg of substance/m3

Inhalation. Long term systemic effects. 114 mg of substance/m3

Soil. 0.63 mg/kg

Fresh water. 0.96 mg/l

Sea water. 0.79 mg/l

Fresh water sediment. 3.6 mg/kg

Marine sediment. 2.9 mg/kg

#### 8.2. Exposure controls

#### Personal protection measures, such as personal protective equipment

Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

## - Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles with protective sides accordance with standard EN166.

In the event of high danger, protect the face with a face shield.

When spraying, wear a face shield in accordance with standard EN166.

Prescription glasses are not considered as protection.

Individuals wearing contact lenses should wear prescription glasses during work where they may be exposed to irritant vapours.

Provide eyewash stations in facilities where the product is handled constantly.

#### - Hand protection

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN374. Gloves must be selected according to the application and duration of use at the workstation.

# SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH) Version : N°1 (18/10/2017) PRODIFA

#### DESODORISANT NOCTURNE 400ML VIS - CTG141657/0/01

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required. Type of gloves recommended :

- Nitrile rubber (butadiene-acrylonitrile copolymer rubber (NBR))

Recommended properties :

- Impervious gloves in accordance with standard EN374

#### - Body protection

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

#### **SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES**

#### 9.1. Information on basic physical and chemical properties

General information :	
Physical state :	Fluid liquid.
	Spray.
Important health, safety and environmental information	
pH :	Not relevant.
Boiling point/boiling range :	78 °C.
Vapour pressure (50°C) :	Not relevant.
Density :	< 1
Water solubility :	Dilutable.
Viscosity:	v < 7 mm2/s (40°C)
Melting point/melting range :	Not specified.
Self-ignition temperature :	200 °C.
Decomposition point/decomposition range :	200 °C.
Chemical combustion heat :	>= 30  kJ/g.
9.2. Other information	

No data available.

## SECTION 10 : STABILITY AND REACTIVITY

## 10.1. Reactivity

No data available.

#### 10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

#### 10.3. Possibility of hazardous reactions

When exposed to high temperatures, the mixture can release hazardous decomposition products, such as carbon monoxide and dioxide, fumes and nitrogen oxide.

#### 10.4. Conditions to avoid

Any apparatus likely to produce a flame or to have a metallic surface at high temperature (burners, electric arcs, furnaces etc.) must not be allowed on the premises.

- Avoid :
- heating
- heat
- accumulation of electrostatic charges.
- flames and hot surfaces

#### **10.5. Incompatible materials**

Keep away from :

- strong acids
- strong oxidising agents

#### 10.6. Hazardous decomposition products

The thermal decomposition may release/form :

- carbon monoxide (CO)
- carbon dioxide (CO2)

## SECTION 11 : TOXICOLOGICAL INFORMATION

#### 11.1. Information on toxicological effects

May have reversible effects on the eyes, such as eye irritation which is totally reversible by the end of observation at 21 days. Splashes in the eyes may cause irritation and reversible damage

#### 11.1.1. Substances

#### Serious damage to eyes/eye irritation :

ETHANOL (CAS: 64-17-5) Causes serious eye irritation. Corneal haze :

 $1 \le$  Average score < 2 and effects totally reversible within 21 days of observation

 $2 \le 4$  Average score < 2.5 and effects totally reversible within 21 days of observation

#### 11.1.2. Mixture

#### **Respiratory or skin sensitisation :**

Conjunctival redness :

Contains at least one sensitising substance. May cause an allergic reaction.

#### Monograph(s) from the IARC (International Agency for Research on Cancer) :

CAS 64-17-5 : IARC Group 1 : The agent is carcinogenic to humans.

#### SECTION 12 : ECOLOGICAL INFORMATION

Harmful to aquatic life with long lasting effects.

The product must not be allowed to run into drains or waterways.

#### 12.1. Toxicity

#### 12.1.2. Mixtures

No aquatic toxicity data available for the mixture.

#### 12.2. Persistence and degradability

No data available.

#### 12.3. Bioaccumulative potential

No data available.

#### 12.4. Mobility in soil

No data available.

## 12.5. Results of PBT and vPvB assessment

No data available.

#### 12.6. Other adverse effects

## SECTION 13 : DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

#### **13.1.** Waste treatment methods

Do not pour into drains or waterways.

#### Waste :

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company. Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

#### Soiled packaging :

Empty container completely. Keep label(s) on container. Give to a certified disposal contractor.

#### **SECTION 14 : TRANSPORT INFORMATION**

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2017 - IMDG 2016 - ICAO/IATA 2017).

## 14.1. UN number

1950

## 14.2. UN proper shipping name

UN1950=AEROSOLS, flammable

### 14.3. Transport hazard class(es)

- Classification :



2.1

#### 14.4. Packing group

-

#### 14.5. Environmental hazards

#### -

#### 14.6. Special precautions for user

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	EQ	Cat.	Tunnel
	2	5F	-	2.1	-	1 L	190 327 344 625	E0	2	D
								_		
IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.	EQ			
	2	See SP63	-	See SP277	F-D,S-U	63 190 277 327	E0			
						344 381 959				
IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note	EQ	
	2.1	-	-	203	75 kg	203	150 kg	A145	E0	
					-			A167		
								A802		
	2.1	-	-	Y203	30 kg G	-	-	A145	E0	
								A167		
								A802		

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.

For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

#### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No data available.

#### **SECTION 15 : REGULATORY INFORMATION**

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### - Classification and labelling information included in section 2:

The following regulations have been used:

## - Directive 75/324/CEE modified by directive 2013/10/UE

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2016/1179. (ATP 9)

#### - Container information:

No data available.

- Particular provisions :

No data available.

#### 15.2. Chemical safety assessment

No data available.

## SECTION 16 : OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

#### Wording of the phrases mentioned in section 3 :

H220	Extremely flammable gas.
H225	Highly flammable liquid and vapour.
H280	Contains gas under pressure; may explode if heated.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

#### Abbreviations :

DNEL : Derived No-Effect Level

PNEC : Predicted No-Effect Concentration

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

WGK : Wassergefahrdungsklasse (Water Hazard Class).

GHS02 : Flame

GHS07 : Exclamation mark

PBT: Persistent, bioaccumulable and toxic.

vPvB : Very persistent, very bioaccumulable.

SVHC : Substances of very high concern.